Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-457-0850

| Cross Sectional Shape: | |
|---|--|
| Round | |
| Thread Class: | |
| 3b 1st end | |
| Thread Direction: | |
| Right-hand 1st end | |
| Inside Diameter: | |
| 0.187 inches | |
| Tempurature Rating: | |
| -65.0 degrees fahrenheit single response and 500.0 degrees fahrenheit single response | |
| Outside Diameter: | |
| 0.312 inches | |
| Minimum Inside Bending Radius: | |
| 2.000 inches | |
| Connection Style: | |
| Plain 2nd end | |
| End Connection Design: | |
| Elbow 2nd end | |
| Connection Type: | |
| Threaded external hose 2nd end | |
| Burst Test Pressure: | |
| 12000.0 pounds per square inch | |
| Maximum Operating Pressure: | |
| 1500.0 pounds per square inch | |
| Thread Size: | |
| 0.437 inches 2nd end | |
| Flow Angle: | |
| 90.0 degrees 2nd end | |
| Inside Surface Condition: | |
| Smooth | |
| Measuring Method And Length: | |
| 18.500 inches | |
| Thread Series Designator: | |
| Unf 2nd end | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A542a0 | |