## NSN 4720-01-458-2798

Nonmetallic Hose Assembly - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4720-01-458-2798                         |  |
|---|--|
| Cross Sectional Shape:  |  |
| Round   |  |
| Thread Class:   |  |
| 3b 1st end  |  |
| Thread Direction:   |  |
| Right-hand 1st end  |  |
| Inside Diameter:  |  |
| 0.602 inches  |  |
| Tempurature Rating:   |  |
| -67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response |  |
| Outside Diameter:   |  |
| 0.750 inches  |  |
| Minimum Inside Bending Radius:  |  |
| 3.880 inches  |  |
| End Application:  |  |
| Tank, abrams m-1  |  |
| Connection Style:   |  |
| Swivel nut, flareless 1st end   |  |
| End Connection Design:  |  |
| Straight 1st end  |  |
| Connection Type:  |  |
| Threaded internal tube 1st end  |  |
| Features Provided:  |  |
| Electrostatic discharge capability  |  |
| Thready Qty Per Inch (tpi):   |  |
| 12 1st end  |  |
| Burst Test Pressure:  |  |
| 12000.0 pounds per square inch  |  |
| Layer Composition And Location:   |  |
| Outer layer braided corrosion resistant steel wire                                    |  |
| Maximum Operating Pressure:   |  |
| 3000.0 pounds per square inch   |  |
| Thread Size:  |  |
| 1.0625 inches 1st end   |  |

Seat Angle:

37.0 degrees 1st end

**Hydrostatic Test Pressure:** 

6000.0 pounds per square inch

**Outer Covering Environmental Protection:** 

Fuel resistant and oil resistant and heat resistant and solvent resistant and vibration resistant

**Inside Surface Condition:** 

Smooth

## NSN 4720-01-458-2798

Nonmetallic Hose Assembly - Page 2 of 2



**Fiig:** A542a0