

View Online at <https://aerobasegroup.com/nsn/4720-01-458-5497>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 257.0 degrees fahrenheit single response

Flange Thickness:

0.625 inches 2nd end

Outside Diameter:

1.850 inches

Minimum Inside Bending Radius:

16.500 inches

Exterior Color:

Black

Flange Outside Diameter:

2.000 inches 2nd end

Connection Style:

Swivel nut flare 1st end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer spirally laid steel wire and 2nd layer spirally laid steel wire and 3rd layer spirally laid steel wire and 4th layer spirally laid steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

1.625 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

124.000 inches

Flange Style:

Round w/ out bolt holes 2nd end

Media For Which Designed:

Fuel/oil, hydrocarbon and water and air single response

Thread Series Designator:

Npt 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0