

View Online at <https://aerobasegroup.com/nsn/4720-01-459-6154>

Cross Sectional Shape:

Round

Thread Class:

2b 2nd end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.750 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response

Outside Diameter:

1.160 inches

Minimum Inside Bending Radius:

9.500 inches

Hose Or Tubing Specification/std Data:

Sae517, 100r2, typeat-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Swivel nut, inverted flare 2nd end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting stainless steel all ends

Connection Type:

Threaded internal pipe 2nd end

Thready Qty Per Inch (tpi):

12 2nd end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

12400.0 pounds per square inch

First End Swivel Action Capability:

Included

Layer Composition And Location:

1st layer braided steel wire err-100

Maximum Operating Pressure:

3100.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Seat Angle:

37.0 degrees 2nd end

Flow Angle:

45.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

70.050 inches

Second End Swivel Action Capability:

Included

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response and air single response and water single response

Thread Series Designator:

Un 2nd end

Specification Data:

Sae517, 100r2, typeat-81343 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0