

View Online at <https://aerobasegroup.com/nsn/4720-01-460-0120>

**Tempurature Rating:**

-2.0 degrees celsius single response and 35.0 degrees celsius single response

**Bolt Hole Diameter:**

0.047 inches 2nd end

**Burst Test Pressure:**

10000.0 pounds per square inch

**Maximum Operating Pressure:**

2500.0 pounds per square inch

**Hydrostatic Test Pressure:**

5000.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Product Name:**

Flexiblehose, internal, 90degrees-90degreeselbow

**Special Features:**

Endfittingsshallmatewithcpvmarkviiiimaleconnector (cage99565); attachmentofhosetohefittingsshallbeeitherpermanentorreusable; tubingandendfittingsandouterbraids shallbemadeof316stainlesssteeliawfed-spec-qq-s-763; hoseandhosecoretubeshallbemadeof'tobedetermined'(tbd) ; weldandinspectiawmil-std-278, classp-1, usingmil-316liawmil-e-19933; weldacceptancecriteriatobeiawmil-std-2035, class1; afterfabrication, hoseandfittings shallbecleanedofsmudges, weldmetal, metalchipsandmoldreleaseagents, oranyothermaterialwhichmightdetractfromintendedoperation, functionorappearanceoftheequipment; threadsshouldhavenoevidenceofcross-threading, detrimental mutilationorhazardousburrs; afterpressuretest, cleanwithgradebwater, conformingtonas-1638, class5; aftercleaning, drywithnitrogen, conformingtobb-n-411, andcaporplugends

**Special Markings:**

Permanentcircumferentialmarkonthehoseatedgeofattachmentfitting, madeattimeofassembly, usedtodetermineanyslippingofhoseintheattachmentfittingduringuse

**Media For Which Designed:**

Air single response and hydraulic fluid single response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0