NSN 4720-01-460-2879

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-460-2879

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:

Tempurature Rating:

-50.0 degrees fahrenheit and 212.0 degrees fahrenheit single response

Outside Diameter:

0.510 inches

0.250 inches

Minimum Inside Bending Radius:

2.000 inches

Connection Style:

Swivel nut, gasket seal 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

18 1st end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer braided wire and outer layer braided polyester cord

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.562 inches 2nd end

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

90.000 inches

Media For Which Designed:

Hydraulic fluid and air and gas and fuel/oil, hydrocarbon and oil, lubricating, diester base single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

NSN 4720-01-460-2879

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A542a0