NSN 4720-01-460-2917

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-460-2917 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -50.0 degrees fahrenheit and 212.0 degrees fahrenheit single response **Outside Diameter:** 0.510 inches **Minimum Inside Bending Radius:** 2.000 inches **Connection Style:** Swivel nut, gasket seal 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 18 1st end **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided wire and outer layer braided polyester cord **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.562 inches 2nd end Flow Angle: 45.0 degrees 2nd end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 64.000 inches Media For Which Designed: Hydraulic fluid and air and gas and fuel/oil, hydrocarbon and oil, lubricating, diester base single response **Thread Series Designator:** Unf 2nd end

N/a

Shelf Life:

NSN 4720-01-460-2917

Nonmetallic Hose Assembly - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0