NSN 4720-01-460-2920

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-460-2920 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.380 inches **Tempurature Rating:** -50.0 degrees fahrenheit and 212.0 degrees fahrenheit single response **Outside Diameter:** 0.670 inches **Minimum Inside Bending Radius:** 2.500 inches **Connection Style:** Swivel nut, gasket seal 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 2nd end **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided wire and outer layer braided polyester cord **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.688 inches 2nd end Flow Angle: 45.0 degrees 2nd end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 47.000 inches Media For Which Designed: Hydraulic fluid and air and gas and fuel/oil, hydrocarbon and oil, lubricating, diester base single response **Thread Series Designator:**

Unf 2nd end

Shelf Life:

N/a

NSN 4720-01-460-2920

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0