NSN 4720-01-460-2926

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-460-2926

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-50.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
0.510 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Swivel nut, gasket seal 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
18 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
1st layer braided wire and outer layer braided polyester cord
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
42.000 inches
Media For Which Designed:
Hydraulic fluid and air and gas and fuel/oil, hydrocarbon and oil, lubricating, diester base single response
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a

NSN 4720-01-460-2926

Nonmetallic Hose Assembly - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A542a0