NSN 4720-01-460-2943

Outer cover perforated polyurethane

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-460-2943

Cross Sectional Shape:					
Round					
Thread Class:					
2b 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.380 inches					
Tempurature Rating:					
-65.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response					
Outside Diameter:					
0.660 inches					
Minimum Inside Bending Radius:					
2.000 inches					
Exterior Color:					
Black					
Connection Style:					
Swivel nut, gasket seal 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded internal tube 1st end					
Thready Qty Per Inch (tpi):					
18 1st end					
Burst Test Pressure:					
9000.0 pounds per square inch					
Layer Composition And Location:					
1st layer braided polyester cord					
Maximum Operating Pressure:					
2250.0 pounds per square inch					
Thread Size:					
0.562 inches 2nd end					
Seat Angle:					
37.0 degrees 2nd end					
Flow Angle:					
45.0 degrees 2nd end					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
669.000 inches					
Special Features:					

NSN 4720-01-460-2943

Nonmetallic Hose Assembly - Page 2 of 2



Me	dia	For	Which	Design	ed:

Hydraulic fluid single response and fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0