NSN 4720-01-460-2943

Outer cover perforated polyurethane

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-460-2943

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.380 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.660 inches |
| Minimum Inside Bending Radius: |
| 2.000 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Swivel nut, gasket seal 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 18 1st end |
| Burst Test Pressure: |
| 9000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided polyester cord |
| Maximum Operating Pressure: |
| 2250.0 pounds per square inch |
| Thread Size: |
| 0.562 inches 2nd end |
| Seat Angle: |
| 37.0 degrees 2nd end |
| Flow Angle: |
| 45.0 degrees 2nd end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 669.000 inches |
| Special Features: |

NSN 4720-01-460-2943

Nonmetallic Hose Assembly - Page 2 of 2



| Media | For | Which | Design | ed: |
|-------|-----|-------|--------|-----|
| | | | | |

Hydraulic fluid single response and fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0