## NSN 4720-01-460-5480

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-460-5480

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-50.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.505 inches
Minimum Inside Bending Radius:
2.000 inches
End Application:
ENDI-TE-MID-ENTI
Connection Style:
Swivel nut, gasket seal 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and outer layer braided polyamide cord
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
12.000 inches
Thread Series Designator:
Unf 2nd end

## NSN 4720-01-460-5480

Nonmetallic Hose Assembly - Page 2 of 2



Spo	ecific	ation	Data:
-----	--------	-------	-------

12361-554 manufacturers standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0