

View Online at <https://aerobasegroup.com/nsn/4720-01-460-8167>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-50.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.570 inches

Minimum Inside Bending Radius:

2.500 inches

End Application:

Nsn2320-01-417-8144, mk15 oskosh truck, model mk15a1

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

16 1st end

Burst Test Pressure:

9000.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and outer layer braided polyamide cord

Maximum Operating Pressure:

2250.0 pounds per square inch

Thread Size:

0.688 inches 1st end

Hydrostatic Test Pressure:

4500.0 pounds per square inch

Outer Covering Environmental Protection:

Weatherproof and abrasion resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

100.000 inches

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0