

View Online at <https://aerobasegroup.com/nsn/4720-01-460-8167>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-50.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Outside Diameter:**

0.570 inches

**Minimum Inside Bending Radius:**

2.500 inches

**End Application:**

Nsn2320-01-417-8144, mk15 oskosh truck, model mk15a1

**Connection Style:**

Swivel nut, gasket seal 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

16 1st end

**Burst Test Pressure:**

9000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided steel wire and outer layer braided polyamide cord

**Maximum Operating Pressure:**

2250.0 pounds per square inch

**Thread Size:**

0.688 inches 1st end

**Hydrostatic Test Pressure:**

4500.0 pounds per square inch

**Outer Covering Environmental Protection:**

Weatherproof and abrasion resistant and oil resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

100.000 inches

**Thread Series Designator:**

Un 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0