Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-461-1126

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
nside Diameter:	
).375 inches	
Fempurature Rating:	
50.0 degrees fahrenheit and 250.0 degrees fahrenheit single response	
Dutside Diameter:	
.690 inches	
Iinimum Inside Bending Radius:	
.500 inches	
Exterior Color:	
Black	
Angle Between Rigid Elbow Fittings In Deg:	
90.0	
End Application:	
2320-01-417-8144	
Connection Style:	
Swivel nut, gasket seal 2nd end	
End Connection Design:	
Elbow 2nd end	
connection Type:	
hreaded internal tube 1st end	
Burst Test Pressure:	
2000.0 pounds per square inch	
ayer Composition And Location:	
st layer rubber composition and 2nd layer rubber impregnated braided corrosion resistant steel w	vire and outer layer rubber composition
laximum Operating Pressure:	
000.0 pounds per square inch	
Thread Size:	
0.688 inches 2nd end	
Flow Angle:	
90.0 degrees 2nd end	
Duter Covering Environmental Protection:	
Abrasion resistant and hydraulic solution resistant	
nside Surface Condition:	
Smooth	
Measuring Method And Length:	
30.000 inches	
Special Features:	
Identifying color black with blue stripe	



Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Nptf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0