NSN 4720-01-461-1299

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-461-1299

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-50.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.690 inches
Minimum Inside Bending Radius:
2.500 inches
Exterior Color:
Black
Angle Between Rigid Elbow Fittings In Deg:
0.0
End Application:
2320-01-417-8144
Connection Style:
Swivel nut, gasket seal 2nd end
End Connection Design:
Elbow 2nd end
Connection Type: Threaded internal tube 1st end
Burst Test Pressure:
12000.0 pounds per square inch Layer Composition And Location:
1st layer rubber composition and 2nd layer rubber impregnated braided corrosion resistant steel wire and outer layer rubber composition
Maximum Operating Pressure:
3000.0 pounds per square inch Thread Size:
0.688 inches 2nd end
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Abrasion resistant and hydraulic solution resistant
Inside Surface Condition:
Smooth Macauting Mathed And Langth:
Measuring Method And Length:
24.000 inches Special Footures
Special Features:

Identifying color black with blue stripe

NSN 4720-01-461-1299

Nonmetallic Hose Assembly - Page 2 of 2



N	Λ	edia	For	Which	Design	ed

Hydraulic fluid single response

Thread Series Designator:

Nptf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0