

View Online at <https://aerobasegroup.com/nsn/4720-01-462-3476>

Cross Sectional Shape:

Round

Inside Diameter:

0.375 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Flange Thickness:

0.375 inches 1st end

Outside Diameter:

1.031 inches

Minimum Inside Bending Radius:

4.000 inches

Flange Outside Diameter:

0.688 inches 1st end

End Application:

M1 abrahms launcher and portable bridge

Connection Style:

Plain swivel w/ gasket groove 1st end

End Flange Construction:

Solid 1st end

End Connection Design:

Straight 1st end

Connection Type:

Plain face flange 1st end

Burst Test Pressure:

16000.0 pounds per square inch

Layer Composition And Location:

1st layer spirally laid corrosion resistant steel wire and 2nd layer spirally laid corrosion resistant steel wire and 3rd layer spirally laid corrosion resistant steel wire and 4th layer spirally laid corrosion resistant steel wire and outer layer rubber impregnated braided fabric

Maximum Operating Pressure:

4000.0 pounds per square inch

Hydrostatic Test Pressure:

8000.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

43.190 inches working

Flange Style:

Round w/ out bolt holes 1st end

Media For Which Designed:

Hydraulic fluid single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0