

View Online at <https://aerobasegroup.com/nsn/4720-01-462-6807>

Cross Sectional Shape:

Round

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.313 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 500.0 degrees fahrenheit single response

Outside Diameter:

0.466 inches

Minimum Inside Bending Radius:

4.000 inches

Angle Between Rigid Elbow Fittings In Deg:

0.0

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

20 1st end

Burst Test Pressure:

9000.0 pounds per square inch

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.234 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Outer Covering Environmental Protection:

Fire resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

17.500 inches working

Thread Tolerance Class:

3a internal 1st end

Special Features:

As1072 fire protection sleeve

Thread Series Designator:

Unj 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-25579 spec.