NSN 4720-01-462-6983

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-462-6983

C	Cross Sectional Shape:
F	Round
T	hread Class:
2	ta 1st end
1	hread Direction:
F	Right-hand 1st end
li	nside Diameter:
1	.000 inches
T	empurature Rating:
	40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
C	Outside Diameter:
1	.475 inches
N	linimum Inside Bending Radius:
1	0.000 inches
E	End Application:
ι	Jsed on spruance class dd (963)
C	Connection Style:
١	lut assembly with gasket 1st end
E	End Connection Design:
5	Straight 1st end
C	Connection Type:
T	Threaded internal hose 1st end
E	Burst Test Pressure:
1	80.0 pounds per square inch
L	ayer Composition And Location:
(Outer layer molded rubber, chloroprene and 1st layer braided polyester cord
N	Maximum Operating Pressure:
9	0.0 pounds per square inch
1	hread Size:
1	.3125 inches 1st end

Seat Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Ozone resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

15.0000 inches excluding end fittings

Special Features:

Trunk and airlock sweep hose assembly on cg-47 & dd-963/993 class u.S. Naval vessels

Media For Which Designed:

Hydraulic fluid single response

NSN 4720-01-462-6983

Nonmetallic Hose Assembly - Page 2 of 2



_		•	_	
ı	hread	Series	1)66	ignator:
•	mcaa	OCI ICS	D C3	igilatoi.

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0