Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-462-7530

Cross	Sectional	Shape:
-------	-----------	--------

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.313 inches

Tempurature Rating:

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Outside Diameter:

0.469 inches

Minimum Inside Bending Radius:

4.000 inches

Exterior Color:

Natural

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

9000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.562 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

35.500 inches working

Nonmetallic Hose Assembly - Page 2 of 2

Special Features:

Has sleeve

Thread Series Designator:

Unjf 1st end

Specification Data:

96906-ms8005 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

