Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-462-8045

Cross Sectio	nal Shape:
Round	
Thread Direc	tion:
Right-hand 1s	at end
Inside Diame	ter:
0.750 inches	
Tempurature	Rating:
-40.0 degrees	fahrenheit and 200.0 degrees fahrenheit single response
Outside Dian	neter:
0.750 inches	
Minimum Ins	ide Bending Radius:
12.000 inches	i i
End Applicat	ion:
	irlock and passageway sweep hose assembly on ddg-31 class us naval vessels
Connection S	
Swivel nut, g	asket seal 2nd end
End Connect	ion Design:
Straight 2nd e	nd
Connection 1	Гуре:
Threaded inte	rnal hose 1st end
Burst Test Pi	ressure:
600.0 pounds	per square inch
Maximum Op	perating Pressure:
300.0 pounds	per square inch
Thread Size:	
0.750 inches	2nd end
Hydrostatic 7	Test Pressure:
300.0 pounds	per square inch
Inside Surfac	e Condition:
Smooth	
Measuring M	ethod And Length:
25.0 feet exc	luding end fittings
Special Featu	ures:
Sonar dome a	irlock and passageway sweep hose assembly for ddg-31 class us naval vessels
Thread Serie	s Designator:
Npt 1st end	
Shelf Life:	
N/a	
Unit Of Meas	ure:
Demilitarizat	ion:
No	

## NSN 4720-01-462-8045

Nonmetallic Hose Assembly - Page 2 of 2

**Fiig:** A542a0

