

View Online at <https://aerobasegroup.com/nsn/4720-01-464-1179>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.430 inches

**Tempurature Rating:**

-65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

**Outside Diameter:**

0.670 inches

**Minimum Inside Bending Radius:**

1.500 inches

**End Application:**

Los angeles class ssn (688), mpp unit 4011

**Burst Test Pressure:**

2200.0 pounds per square inch single response

**Layer Composition And Location:**

1st layer molded rubber, ethylene propylene or 2nd layer braided synthetic cord or 3rd layer braided synthetic cord

**Maximum Operating Pressure:**

600.0 pounds per square inch single response

**Outer Covering Environmental Protection:**

Corrosion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

19.500 inches

**Product Name:**

Straight swivel, flareless connection

**Special Features:**

Weight per ft 0.10, fitting material stainless (cres316), pressure rating 550.0 psi, media designed for hydraulic fluid and liquid coolant, flexible; inner conveying tube material: ethylene propylene rubber

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A541z0