Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-465-0084

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.219 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit	and 250.0 degrees fahrenheit single response
Outside Diameter:	
0.440 inches	
Minimum Inside Bending	Radius:
2.000 inches	
Connection Style:	
Swivel nut with compression	on sleeve 1st end
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st	end
Burst Test Pressure:	
6000.0 pounds per square	inch
Layer Composition And	Location:
1st layer rubber impregnat	ed braided corrosion resistant steel wire and outer layer spirally laid corrosion resistant steel wire
Maximum Operating Pres	ssure:
1000.0 pounds per square	inch
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressur	·e:
3000.0 pounds per square	inch
Inside Surface Condition	:
Smooth	
Measuring Method And L	_ength:
20.875 inches	
Special Test Features:	
Hose cert to faa tso-c53a t	ype a
Thread Series Designato	r:
Unjf 1st end	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0