Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-465-1825

| Cross Sectional Shape: |
|--|
| Round |
| |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.880 inches |
| Tempurature Rating: |
| -40.000 degrees fahrenheit single response and 300.000 degrees fahrenheit single response |
| Outside Diameter: |
| 1.240 inches |
| Minimum Inside Bending Radius: |
| 3.500 inches |
| End Application: |
| F/a-18 hornet aircraft |
| Connection Style: |
| Swivel, plain 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external hose 1st end |
| Features Provided: |
| Reusable end fittings |
| Burst Test Pressure: |
| 1600.000 pounds per square inch |
| Maximum Operating Pressure: |
| 400.000 pounds per square inch |
| Thread Size: |
| 1.312 inches 1st end |
| Criticality Code Justification: |
| Feat |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 24.000 inches |
| Special Features: |
| Weapon system essential; 4 ply brass plated steel wire reinforcement, braided refractory insulation hose |
| Media For Which Designed: |
| Oil, lubricating, diester base single response |
| Thread Series Designator: |
| Jic 1st end |
| Shelf Life: |
| N/a |
| |

NSN 4720-01-465-1825

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0