## NSN 4720-01-465-2132

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-465-2132
Cross Sectional Shape:
Round
Thread Direction:
Right-hand 2nd end
Inside Diameter:
1.000 inches
Tempurature Rating:
300.0 degrees fahrenheit single response
Outside Diameter:
1.480 inches
Minimum Inside Bending Radius:
12.000 inches
Flange Outside Diameter:
1.870 inches 1st end
End Application:
Fire fighting equipment
Connection Style:
Plain 2nd end
End Flange Construction:
Solid 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external hose 2nd end
Thready Qty Per Inch (tpi):
12 2nd end
Burst Test Pressure:
16000.0 pounds per square inch
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
1.438 inches 2nd end
Flow Angle:
90.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
58.000 inches
Flange Style:
Round w/ out bolt holes 1st end
Supplementary Features:
Nha p/n 9325-03-1020-01; vendor fitting p/n 1b16fh316, style sfb, vendor fitting p/n 1ba16fr16, style ors; hose p/n gh493-16, cagec
01276, niin01-450-8466

## NSN 4720-01-465-2132

Nonmetallic Hose Assembly - Page 2 of 2



_		•	_	
ı	hread	Series	1)66	ignator:
•	mcaa	OCI ICS	000	igilatoi.

Un 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0