NSN 4720-01-465-2273

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-465-2273

| Cross Sectional Shape: |
|--|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.380 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.690 inches |
| Minimum Inside Bending Radius: |
| 2.500 inches |
| End Application: |
| Fire fighting equipment |
| Connection Style: |
| Plain 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external hose 1st end |
| Thready Qty Per Inch (tpi): |
| 18 1st end |
| Burst Test Pressure: |
| 20000.0 pounds per square inch |
| Maximum Operating Pressure: |
| 5000.0 pounds per square inch |
| Thread Size: |
| 0.562 inches 1st end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 34.500 inches |
| Media For Which Designed: |
| Hydraulic fluid, water base single response |
| Supplementary Features: |
| Nha p/n 9325-03-1010-01; vendor fitting p/n 1aa6fj6, style fj, vendor fitting p/n 1aa6fj6, style fj; hose p/n gh781-6, cagec 01276, niin |
| 01-384-6249 |
| Thread Series Designator: |
| Un 1st end |
| Shelf Life: |

NSN 4720-01-465-2273

Nonmetallic Hose Assembly - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A542a0