NSN 4720-01-465-2279

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-465-2279
Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.380 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response
Outside Diameter:
0.690 inches
Minimum Inside Bending Radius:
2.500 inches
End Application:
Fire fighting equipment
Connection Style:
Plain 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external hose 1st end
Burst Test Pressure:
20000.0 pounds per square inch
Maximum Operating Pressure:
5000.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
53.000 inches
Media For Which Designed:
Hydraulic fluid, water base single response
Supplementary Features:
Nha p/n 9325-03-1010-01; vendor fitting p/n 1aa6fj6, style fj, vendor fitting p/n 1aa6fjc6, style fjc; hose p/n gh781-6, cagec 01276, niin
01-384-6249
Thread Series Designator:
Unf 2nd end
Shelf Life:

N/a

NSN 4720-01-465-2279

Nonmetallic Hose Assembly - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0