Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-465-2284

Cross Sectional Shape:	
Round	
Thread Class:	
2b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.380 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response	
Outside Diameter:	
0.690 inches	
Minimum Inside Bending Radius:	
2.500 inches	
End Application:	
Fire fighting equipment	
Connection Style:	
Plain 1st end	
End Connection Design:	
Straight 1st end	
End Fitting Component And Material:	
Complete fitting steel all ends	
Fitting Component And Surface Treatment:	
Complete fitting zinc 1st end	
Connection Type:	
Threaded external hose 1st end	
Thready Qty Per Inch (tpi):	
18 1st end	
Second End Relationship With First End:	
Identical	
Burst Test Pressure:	
20000.0 pounds per square inch	
First End Swivel Action Capability:	
Included	
Maximum Operating Pressure:	
5000.0 pounds per square inch	
Thread Size:	
0.562 inches 1st end	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
177.500 inches	

NSN 4720-01-465-2284

Nonmetallic Hose Assembly - Page 2 of 2



Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Hydraulic fluid, water base single response

Supplementary Features:

Nha p/n 9325-03-1010-01; vendor fitting p/n 1aa6fj6, style fj, vendor fitting p/n 1aa6fj6, style fj; hose p/n gh781-6, cagec 01276, niin 01-384-6249

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0