

View Online at <https://aerobasegroup.com/nsn/4720-01-465-2555>

**Cross Sectional Shape:**

Round

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

Between 0.173 inches and 0.203 inches

**Temperature Rating:**

-65.000 degrees fahrenheit and 450.000 degrees fahrenheit single response

**Outside Diameter:**

Between 0.304 inches and 0.343 inches

**Minimum Inside Bending Radius:**

2.000 inches

**Exterior Color:**

Black

**End Application:**

2815-01-414-6821; wsd: recovery vehicle fu

**Connection Style:**

Flared 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded external tube 1st end

**Features Provided:**

Electrostatic discharge capability

**Burst Test Pressure:**

12000.000 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1500.000 pounds per square inch

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

7000.000 pounds per square inch

**Flow Angle:**

45.000 degrees 2nd end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

100.000 inches working

**Thread Series Designator:**

Unjf 1st end

**Specification Data:**

96906-ms8005 government standard and 96906-mil-s8879 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0