

View Online at <https://aerobasegroup.com/nsn/4720-01-465-2555>

Cross Sectional Shape:

Round

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.173 inches and 0.203 inches

Temperature Rating:

-65.000 degrees fahrenheit and 450.000 degrees fahrenheit single response

Outside Diameter:

Between 0.304 inches and 0.343 inches

Minimum Inside Bending Radius:

2.000 inches

Exterior Color:

Black

End Application:

2815-01-414-6821; wsd: recovery vehicle fu

Connection Style:

Flared 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external tube 1st end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

12000.000 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.000 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

7000.000 pounds per square inch

Flow Angle:

45.000 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

100.000 inches working

Thread Series Designator:

Unjf 1st end

Specification Data:

96906-ms8005 government standard and 96906-mil-s8879 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0