## NSN 4720-01-465-3665

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-465-3665

One of Oceanies and Observed
Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.000 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response
Outside Diameter:
1.520 inches
Minimum Inside Bending Radius:
12.000 inches
End Application:
Fire fighting equipment
Connection Style:
Nut assembly with gasket 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal hose 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
20000.0 pounds per square inch
Maximum Operating Pressure:
5000.0 pounds per square inch
Thread Size:
1.438 inches 1st end
Flow Angle:
45.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
55.000 inches
Media For Which Designed:
Hydraulic fluid, water base single response
Supplementary Features:
Nha p/n 9325-03-1020-01; fitting p/n fj9718-1616s, style ors, fc5327-1616-s, style sfa, hose p/n fc273-16, cagec 01276
Thread Series Designator:
Un 1st end

## NSN 4720-01-465-3665

Nonmetallic Hose Assembly - Page 2 of 2



	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0