NSN 4720-01-465-3743

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-465-3743

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.380 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response
Outside Diameter:
0.690 inches
Minimum Inside Bending Radius:
2.500 inches
End Application: Eiro fighting equipment
Fire fighting equipment Connection Style:
Nut assembly with gasket 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal hose 1st end
Burst Test Pressure:
20000.0 pounds per square inch
Maximum Operating Pressure:
5000.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Flow Angle:
90.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
29.000 inches
Media For Which Designed:
Hydraulic fluid, water base single response
Supplementary Features:
Nha p/n 9325-03-1020-01; fitting p/ns 1aa6fjb6, style fjb, 1aa6fj6fj, hose p/n gh 781-6, cagec 01276, niin 01-384-6249
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a

NSN 4720-01-465-3743

Nonmetallic Hose Assembly - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A542a0