NSN 4720-01-465-3880

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-465-3880

| Round |
|--|
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.620 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.930 inches |
| Minimum Inside Bending Radius: |
| 3.000 inches |
| End Application: |
| Fire fighting equipment |
| Connection Style: |
| Nut assembly with gasket 2nd end |
| End Connection Design: |
| Straight 2nd end |
| Connection Type: |
| Threaded internal hose 1st end |
| Burst Test Pressure: |
| 14500.0 pounds per square inch |
| Maximum Operating Pressure: |
| 4250.0 pounds per square inch |
| Thread Size: |
| 0.875 inches 2nd end |
| Flow Angle: |
| 90.0 degrees 1st end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 180.000 inches |
| Media For Which Designed: |
| Hydraulic fluid, water base single response |
| Supplementary Features: |
| Nha p/n 9325-03-1020-01; fitting p/ns 1aa8fja8, style fj, 1aa8fj8, fj; hose p/n gh781-8, cagec 01276 |
| Thread Series Designator: |
| Unf 2nd end |
| Shelf Life: |
| N/a |
| |

NSN 4720-01-465-3880

Nonmetallic Hose Assembly - Page 2 of 2



| U | n | it | Of | Μe | eas | ur | e: |
|---|---|----|----|----|-----|----|----|
| | | | | | | | |

--

Demilitarization:

No

Fiig:

A542a0