Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-465-3882

Cross Sectional Shape: Round Thread Class: 2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.750 inches Tempurature Rating: -40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response Outside Diameter: 0.930 inches Minimum Inside Bending Radius: 4.750 inches End Application: Fire fighting equipment Connection Style: Nut assembly with gasket 2nd end End Connection Design: Straight 2nd end Connection Type: Threaded internal hose 1st end
Thread Class:2b 1st endThread Direction:Right-hand 1st endInside Diameter:0.750 inchesTempurature Rating:-40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single responseOutside Diameter:0.930 inchesMinimun Inside Bending Radius:4.750 inchesEnd Application:Fire fighting equipmentConnection Style:Nut assembly with gasket 2nd endEnd Connection Design:Straight 2nd endConnection Type:
2b 1st endThread Direction:Right-hand 1st endInside Diameter:0.750 inchesTempurature Rating:-40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single responseOutside Diameter:0.930 inchesMinimum Inside Bending Radius:4.750 inchesEnd Application:Fire fighting equipmentConnection Style:Nut assembly with gasket 2nd endEnd Connection Design:Straight 2nd endConnection Type:
Thread Direction: Right-hand 1st end Inside Diameter: 0.750 inches Tempurature Rating: -40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response Outside Diameter: 0.930 inches Minimum Inside Bending Radius: 4.750 inches End Application: Fire fighting equipment Connection Style: Nut assembly with gasket 2nd end End Connection Design: Straight 2nd end Connection Type:
Right-hand 1st endInside Diameter:0.750 inchesTempurature Rating:-40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single responseOutside Diameter:0.930 inchesMinimum Inside Bending Radius:4.750 inchesEnd Application:Fire fighting equipmentConnection Style:Nut assembly with gasket 2nd endEnd Connection Design:Straight 2nd endConnection Type:
Inside Diameter: 0.750 inches Tempurature Rating: -40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response Outside Diameter: 0.930 inches Minimum Inside Bending Radius: 4.750 inches End Application: Fire fighting equipment Connection Style: Nut assembly with gasket 2nd end End Connection Design: Straight 2nd end Connection Type:
0.750 inches Tempurature Rating: -40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response Outside Diameter: 0.930 inches Minimum Inside Bending Radius: 4.750 inches End Application: Fire fighting equipment Connection Style: Nut assembly with gasket 2nd end End Connection Design: Straight 2nd end Connection Type:
Tempurature Rating:-40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single responseOutside Diameter:0.930 inches0.930 inchesMinimum Inside Bending Radius:4.750 inchesEnd Application:Fire fighting equipmentConnection Style:Nut assembly with gasket 2nd endEnd Connection Design:Straight 2nd endConnection Type:
 -40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response Outside Diameter: 0.930 inches Minimum Inside Bending Radius: 4.750 inches End Application: Fire fighting equipment Connection Style: Nut assembly with gasket 2nd end End Connection Design: Straight 2nd end Connection Type:
Outside Diameter:0.930 inchesMinimum Inside Bending Radius:4.750 inchesEnd Application:Fire fighting equipmentConnection Style:Nut assembly with gasket 2nd endEnd Connection Design:Straight 2nd endConnection Type:
0.930 inches Minimum Inside Bending Radius: 4.750 inches End Application: Fire fighting equipment Connection Style: Nut assembly with gasket 2nd end End Connection Design: Straight 2nd end Connection Type:
Minimum Inside Bending Radius: 4.750 inches End Application: Fire fighting equipment Connection Style: Nut assembly with gasket 2nd end End Connection Design: Straight 2nd end Connection Type:
4.750 inches End Application: Fire fighting equipment Connection Style: Nut assembly with gasket 2nd end End Connection Design: Straight 2nd end Connection Type:
End Application:Fire fighting equipmentConnection Style:Nut assembly with gasket 2nd endEnd Connection Design:Straight 2nd endConnection Type:
Fire fighting equipment Connection Style: Nut assembly with gasket 2nd end End Connection Design: Straight 2nd end Connection Type:
Connection Style: Nut assembly with gasket 2nd end End Connection Design: Straight 2nd end Connection Type:
Nut assembly with gasket 2nd end End Connection Design: Straight 2nd end Connection Type:
End Connection Design: Straight 2nd end Connection Type:
Straight 2nd end Connection Type:
Connection Type:
Threaded internal hose 1st end
Burst Test Pressure:
14500.0 pounds per square inch
Maximum Operating Pressure:
3125.0 pounds per square inch
Thread Size:
0.875 inches 2nd end
Flow Angle:
90.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
14.000 inches
Media For Which Designed:
Hydraulic fluid, water base single response
Supplementary Features:
Nha p/n 9325-03-1020-01; fitting p/ns 1aa12fja12, style fja, 1aa12fj12, fj; hose p/n gh781-12, cagec 01276
Thread Series Designator:
mituu oonoa beaignator.
Unf 2nd end
-

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0