

View Online at <https://aerobasegroup.com/nsn/4720-01-465-5669>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.547 inches

Outside Diameter:

0.344 inches

Minimum Inside Bending Radius:

2.500 inches

Angle Between Rigid Elbow Fittings In Deg:

28.0

End Application:

Oh-58d, helicopter, observation (ahip)

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

3600.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

600.0 pounds per square inch

Thread Size:

0.375 inches 1st end

Seat Angle:

37.0 degrees 1st end

Flow Angle:

90.0 degrees 1st end

Measuring Method And Length:

26.500 inches working

Product Name:

Hose assembly-non fire resistant, flared, rubber

Special Features:

Shall be faa-tso-c53a type a certified with tso tag attached; when ordering identify with bell standard part number from the sources listed on qpl of bhtl procurement specification 299-947-045 only

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0