

View Online at <https://aerobasegroup.com/nsn/4720-01-465-5699>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.641 inches

**Outside Diameter:**

0.438 inches

**Minimum Inside Bending Radius:**

3.500 inches

**End Application:**

Oh-58d, helicopter, observation (ahip)

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

3600.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

600.0 pounds per square inch

**Thread Size:**

0.500 inches 2nd end

**Seat Angle:**

37.0 degrees 2nd end

**Flow Angle:**

90.0 degrees 2nd end

**Measuring Method And Length:**

16.000 inches working

**Product Name:**

Hose assembly - non fire resistant, flared, rubber

**Special Features:**

Shall be faa-tso-c53a type a certified with tso tag attached; when ordering identify with bell standard part number from the sources listed on qpl of bhti procurement specification 299-947-045 only

**Thread Series Designator:**

Unjf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0