

View Online at <https://aerobasegroup.com/nsn/4720-01-465-6070>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.750 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Outside Diameter:

1.250 inches

End Application:

5420-01-430-5403, carrier, bridge launching, p/n lscp94001, cagec 19207

Connection Style:

Swivel nut, flareless 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

5000.0 pounds per square inch

Maximum Operating Pressure:

1700.0 pounds per square inch

Thread Size:

1.312 inches 1st end

Seat Angle:

12.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

22.720 inches and 23.220 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Supplementary Features:

Max proof pressure 3400.0 psi; polyester chafe guard: operating temperature m65.0 f to 300.0 f; must meet 1000, 000 cycles per arp-1536; color blue; nha p/n 12281810

Thread Series Designator:

Un 1st end

Specification Data:

81349-mil-h-25579 government specification

Specification Or Standard:

1 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0