Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-465-6300

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| |
| Right-hand 1st end Inside Diameter: |
| 0.313 inches |
| |
| Tempurature Rating: |
| -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: |
| 0.446 inches |
| |
| Annimum Inside Bending Radius: |
| |
| End Application: |
| Oh-58d, helicopter, observation (ahip) |
| Connection Style: |
| Swivel nut, flareless 2nd end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 6500.0 pounds per square inch |
| Maximum Operating Pressure: |
| 1500.0 pounds per square inch Thread Size: |
| |
| 0.563 inches 2nd end |
| Seat Angle: |
| 12.0 degrees 2nd end |
| Flow Angle: |
| 90.0 degrees 2nd end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 25.000 inches working |
| Product Name: |
| Hose assembly, tfe, flareless, high temp, medium pressure |
| Special Features: |
| HOSE-AS-SEM-BLYS |
| Thread Series Designator: |
| Unjf 1st end |

NSN 4720-01-465-6300

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-25579 spec.

