NSN 4720-01-465-6323

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-465-6323
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
2.000 inches
End Application:
Oh-58d, helicopter, observation (ahip)
Connection Style:
Swivel nut, flareless 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
6500.0 pounds per square inch
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
12.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
16.000 inches working
Product Name:
Hose assembly, tfe, flareless, high temp, medium pressure
Special Features:
Hose assembly shall be certified to faa tso-c53a, type b - by tso tag attached; procurement - any source qualified to mil-h-25579; can be
fabricated from hose nsn 4720-00-8571736+ straight fitting nsn 4730-00-877987 (2)
Thread Series Designator:
Unjf 1st end
Shelf Life:

N/a

NSN 4720-01-465-6323

Nonmetallic Hose Assembly - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-25579 spec.