Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-465-9062

Cross Sectional Shape: Round Inside Diameter: 0.375 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.490 inches Minimum Inside Bending Radius: 2.500 inches End Application: Special forces equipment/equipage
Inside Diameter: 0.375 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.490 inches Minimum Inside Bending Radius: 2.500 inches End Application: Special forces equipment/equipage
0.375 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.490 inches Minimum Inside Bending Radius: 2.500 inches End Application: Special forces equipment/equipage
Tempurature Rating:         -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response         Outside Diameter:         0.490 inches         Minimum Inside Bending Radius:         2.500 inches         End Application:         Special forces equipment/equipage
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.490 inches Minimum Inside Bending Radius: 2.500 inches End Application: Special forces equipment/equipage
Outside Diameter: 0.490 inches Minimum Inside Bending Radius: 2.500 inches End Application: Special forces equipment/equipage
0.490 inches Minimum Inside Bending Radius: 2.500 inches End Application: Special forces equipment/equipage
Minimum Inside Bending Radius: 2.500 inches End Application: Special forces equipment/equipage
2.500 inches End Application: Special forces equipment/equipage
End Application: Special forces equipment/equipage
Special forces equipment/equipage
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external hose 1st end
Burst Test Pressure:
14000.0 pounds per square inch
Maximum Operating Pressure:
5000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
504.000 inches
Supplementary Features:
Designed for multi-purpose media; connection type 0.375 cpv threads
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0