NSN 4720-01-466-2678

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-466-2678

Cross Sectional Shape:
Round
Inside Diameter:
1.250 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Flange Thickness:
0.315 inches 1st end
Outside Diameter:
1.850 inches
Minimum Inside Bending Radius:
16.500 inches
Exterior Color:
Black
Flange Outside Diameter:
2.000 inches 1st end
Connection Style:
Straight 2nd end
End Flange Construction:
Solid 1st end
End Connection Design:
Straight 1st end
Connection Type:
Unthreaded external hose 2nd end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
1st layer molded rubber and 2nd layer spirally laid steel wire and 3rd layer spirally laid steel wire and 4th layer spirally laid steel wire and
5th layer spirally laid steel wire and outer layer molded rubber
Maximum Operating Pressure:
4000.0 pounds per square inch
Hydrostatic Test Pressure:
8000.0 pounds per square inch
Outer Covering Environmental Protection:
Weatherproof and oil resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
36.000 inches
Flange Style:
Round w/ out bolt holes 1st end

1.250 inches 2nd end

Inside Diameter Hose Accommodated:

NSN 4720-01-466-2678

Nonmetallic Hose Assembly - Page 2 of 2



Spe	cial	Features	s:

One end hasno fitting

Media For Which Designed:

Hydraulic fluid single response

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0