

View Online at <https://aerobasegroup.com/nsn/4720-01-466-2736>

Cross Sectional Shape:

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.407 inches

Minimum Inside Bending Radius:

1.500 inches

End Application:

USED-ON-NSN-2330

Connection Style:

Swivel nut, inverted flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

24 1st end

Burst Test Pressure:

1400.0 pounds per square inch

Layer Composition And Location:

1st layer plastic, polyvinyl chloride and 2nd layer braided fiber and outer layer molded rubber

Maximum Operating Pressure:

150.0 pounds per square inch

Thread Size:

0.375 inches 1st end

Seat Angle:

37.0 degrees 1st end

Outer Covering Environmental Protection:

Hydraulic solution resistant and oil resistant and water resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

15.000 inches

Media For Which Designed:

Air single response

Thread Series Designator:

Uns 1st end

Specification Data:

81343-sae j517, j516 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0