

View Online at <https://aerobasegroup.com/nsn/4720-01-466-2736>

**Cross Sectional Shape:**

Round

**Thread Class:**

2a 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.375 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.407 inches

**Minimum Inside Bending Radius:**

1.500 inches

**End Application:**

USED-ON-NSN-2330

**Connection Style:**

Swivel nut, inverted flare 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

24 1st end

**Burst Test Pressure:**

1400.0 pounds per square inch

**Layer Composition And Location:**

1st layer plastic, polyvinyl chloride and 2nd layer braided fiber and outer layer molded rubber

**Maximum Operating Pressure:**

150.0 pounds per square inch

**Thread Size:**

0.375 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Outer Covering Environmental Protection:**

Hydraulic solution resistant and oil resistant and water resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

15.000 inches

**Media For Which Designed:**

Air single response

**Thread Series Designator:**

Uns 1st end

**Specification Data:**

81343-sae j517, j516 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0