

View Online at <https://aerobasegroup.com/nsn/4720-01-466-2764>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

Outside Diameter:

0.343 inches

Minimum Inside Bending Radius:

2.000 inches

End Application:

Gfe apl chang, spruance class dd (963)

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Thready Qty Per Inch (tpi):

20 2nd end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer molded polytetrafluoroethylene and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Criticality Code Justification:

Feat

Inside Surface Condition:

Smooth

Measuring Method And Length:

63.000 inches working

Product Name:

Hose assembly, tfe, medium pressure, crimped

Special Features:

Weapon system essential

Media For Which Designed:

Air and hydraulic fluid single response

Thread Series Designator:

Unjf 1st end

Specification Data:

96906-ms8005-4c government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0