

View Online at <https://aerobasegroup.com/nsn/4720-01-466-2841>

Cross Sectional Shape:

Round

Thread Class:

2b 2nd end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.000 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response

Outside Diameter:

1.480 inches

Minimum Inside Bending Radius:

6.000 inches

Exterior Color:

Black

Hose Or Tubing Specification/std Data:

Sae j517, 81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

First End Fitting Specification/std Data:

Sae j516, 81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Swivel nut, inverted flare 2nd end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Threaded internal tube 2nd end

Thready Qty Per Inch (tpi):

12 2nd end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

12000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer molded rubber, synthetic err-100

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

1.313 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and oil resistant and weatherproof and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

56.000 inches

Second End Swivel Action Capability:

Not included

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Un 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0