## NSN 4720-01-466-2935

24.000 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-466-2935

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
1.140 inches
Minimum Inside Bending Radius:
4.750 inches
Exterior Color:
Black
Connection Style: Swivel nut, inverted flare 1st end
End Connection Design:
Straight 1st end Connection Type:
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
1st layer molded rubber, synthetic and 2nd layer braided steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
1.063 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant and weatherproof and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:

## NSN 4720-01-466-2935

Nonmetallic Hose Assembly - Page 2 of 2



Me	dia	For	Which	Design	ed:

Hydraulic fluid single response

**Thread Series Designator:** 

Un 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0