NSN 4720-01-466-3927

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-466-3927

| Cross Sectional Shape: |
|---|
| Round |
| Inside Diameter: |
| 0.380 inches |
| |
| Tempurature Rating: |
| -40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response Outside Diameter: |
| 0.840 inches |
| |
| Minimum Inside Bending Radius: |
| 5.000 inches |
| Exterior Color: |
| Blue |
| End Application: |
| 2320-01-417-3180 power unit, front, p/n 1500, cagec 45152, mk48, oshkosh truck corp, model mk48a1, id no 08780b |
| Burst Test Pressure: |
| 16000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer molded rubber, synthetic err-100 |
| Maximum Operating Pressure: |
| 5000.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 24.000 inches excluding end fittings |
| Product Name: |
| Test hose assembly |
| Special Features: |
| Inner conveying tube material-rubber, synthetic |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A542a0 |
| |