

View Online at <https://aerobasegroup.com/nsn/4720-01-466-5279>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.625 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

**Outside Diameter:**

0.812 inches

**Minimum Inside Bending Radius:**

6.000 inches

**Quick Disconnect Size:**

0.750 inches 1st end

**End Application:**

Tools/equipment, ticonderoga class cg (47)

**Connection Style:**

Push (external) 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

External quick disconnect 1st end

**Burst Test Pressure:**

6000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided steel wire

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

9.000 inches

**Product Name:**

Flex line 3/4

**Special Features:**

Connects to female swagelok quick-connect coupler only, provides leak free performance, can be used with high purity fluids (food, drink, etc)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0