

View Online at <https://aerobasegroup.com/nsn/4720-01-466-7928>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.688 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.938 inches

Minimum Inside Bending Radius:

4.500 inches

End Application:

1520-01-125-5476; helicopter, observation (ahip); oh-58d

Connection Style:

Swivel nut with compression sleeve 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

3750.0 pounds per square inch

Layer Composition And Location:

1st layer rubber impregnated braided corrosion resistant steel wire and 2nd layer spirally laid corrosion resistant steel wire

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

1.0625 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

15.500 inches

Special Features:

Part number formatted iaw bht specification 299-947-045; assembly certified faa tso-c53a type a

Thread Series Designator:

Unj 1st end

Specification Data:

Saej516-81343 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0