NSN 4720-01-467-1684

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-467-1684 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.219 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response **Outside Diameter:** 0.440 inches **Minimum Inside Bending Radius:** 2.000 inches Angle Between Rigid Elbow Fittings In Deg: 45.0 **End Application:** Helicopter observation, oh-58d **Connection Style:** Swivel nut with compression sleeve 2nd end **End Connection Design:** Elbow 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 6000.0 pounds per square inch **Layer Composition And Location:** 1st layer rubber impregnated braided corrosion resistant steel wire and outer layer spirally laid corrosion resistant steel wire **Maximum Operating Pressure:** 1000.0 pounds per square inch

Thread Size:

0.437 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

19.000 inches

NSN 4720-01-467-1684

Nonmetallic Hose Assembly - Page 2 of 2



	••		•	_		
ı	hre	ลด	Seri	26 I I	PSIU	nator:
•		uu	CCII		COIG	mator.

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0